

Vertical Hole Spacing

Non cumulative tolerances on hole to hole spacing.


	Metric (mm)	Decimal (in.)
A	2414.0 ±0.00	95.039 ±0.000
B	40.0 ±.25	1.575 ±.010
C	85.0 ±.20	3.346 ±.008
D	200.0 ±.20	7.874 ±.008
E	260.0 ±.20	10.236 ±.008
F	277.0 ±.20	10.906 ±.008
H	38.1 ±.20	1.500 ±.008
M	38.6 ±.025	1.520 ±.010
N	209.6 ±.020	8.250 ±.008
O	247.7 ±.020	9.750 ±.008
P	260.1 ±.020	10.250 ±.008
Q	304.8 ±.020	12.000 ±.008
R	210.1 ±.020	8.270 ±.008
S	263.5 ±.020	10.375 ±.008
T	387.4 ±.020	15.250 ±.008
U	346.1 ±.020	13.625 ±.008

1/4-20 Sex Bolt (9 places)

#12 x 82" F.H. countersunk wood or machine screws, (27 places).

37 bearings spaced evenly @ 2.563" center to center.

OPTIONAL: #12 Pan Head Drill-kwik Screws



1.020" [25.9mm] Ref.
End of hinge to first bearing, both ends.

Unless noted all dimensions ±.020" ±.5mm