

GYQS7.R27068 - Electrically Controlled Single-point Locks and Latches Certified for Canada

Electrically Controlled Single-point Locks and Latches Certified for Canada

See General Information for Electrically Controlled Single-point Locks and Latches Certified for Canada

CAL-ROYAL PRODUCTS INC

R27068

6605 FLOTILLA ST
COMMERCE, CA 90040-1815 USA

Cylindrical electrified type, with 1/2 in. latch bolt throw, Model(s) CR6000, for use with doors not exceeding 4 feet (1219 mm) in width and 8 feet (2438 mm) in height rated up to and including 3 hrs.

Cylindrical electrified type, with 1/2 in. latch bolt throw, Model(s) CR9000, for use with doors not exceeding 4 feet (1219 mm) in width and 8 feet (2438 mm) in height rated up to and including 20 minutes.

Cylindrical type, with a 3/4 in. (19mm) latch bolt, Model(s) CR3000

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MX-SC8070, for use with doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MX-SC8080, for use with doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MX-SC8080-M, for use with doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MX-SC8082, for use with doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MX-SC8082-M, for use with doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MX-SC8480, for use with doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. (19 mm) latch bolts, Model(s) MX-SC8485, for use with doors rated up to 3 hrs and measuring up to 4 ft (1220 mm) wide and 8 ft (2438 mm) high.

Mortise type, with 3/4 in. latch bolts, rated 12 Vdc, 0.6 A or 24 Vdc, 0.3 A, Model(s) SC400, SC404, SC408 SC412

Last Updated on 2020-05-13

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"