



# INSTRUCTION FOR CAL-ROYAL OUTSIDE PULL TRIM

## For 9800/9860V Series Rim and Vertical Rod Device

	9800NL	9800DTP	9800EOP
<p>Cup washer &amp; screws</p> <p>Vertical Chassis Centerline</p> <p>Cylinder Nut</p> <p>Cylinder Back Plate</p> <p>Cylinder screw</p> <p>Rim Cylinder</p>	<p>Outside by Pull &amp; Key Key retracts latchbolt. Night Latch Pull Trim with Cyl.</p>	<p>Outside by Pull only Pull when dogged</p>	<p>Outside by Cover Plate only</p>
	<p><b>03 Function Night Latch</b></p>	<p><b>02 Function Pull</b></p>	<p><b>10 Function Cover Plate</b></p>
	<p>Attach collar, back plate and rim cylinder to the trim plate with the (2) cylinder screws. attach to door thru bolting the (2) screws to the chassis &amp; (2) cup washer &amp; screws at the bottom to the door. covers 161 cut out</p>	<p>Attach trim to door thru bolting the (2) screws to the chassis. &amp; (2) cup washers and screws at the bottom to the door covers 161 cut out</p>	<p>Attach trim to door thru bolting the (2) screws to the chassis. and screws at the bottom to the door covers 161 cut out</p>