



DIMENSIONS SHOWN ON THIS TEMPLATE ARE FOR TOP FLUSH BOLTS. FOR BOTTOM BOLTS INVERT AND MEASURE FROM BOTTOM EDGE OF DOOR

ACTIVE DOOR STRIKE
2 EACH #8 x 3/4"

FRAME & SILL STRIKE
2 EACH #8 x 3/4"

TOP & BOTTOM BOLT HD. GUIDE
3 EACH #10 x 7/8"

BOLT HOUSING
2 EACH #8 x 3/4"
2 EACH #8-32 x 1/4"

SCREW DETAILS:	
Bolt Housing	:2 - #8 x 3/4" flat head sheet metal/machine screws
	2 - #8-32 x 3/8" flat head sheet metal screws
Frame & Sill Strike	:2 - #8 x 3/4" flat head sheet metal/machine screws
Reversible Bolt Guide	:2 - #8 x 3/4" flat head sheet metal/machine screws
Active Door Strike	:2 - #8 x 3/4" flat head sheet metal/machine screws



6605 Flotilla St.
City of Commerce
CA 90040 USA
Tel: (323) 888-6601
FAX: (323) 888-6699
Website: cal-royal.com
Email: sales@cal-royal.com

ITEM NO.:	DESCRIPTION:	SCALE:
AUTOFLW-22	AUTOMATIC FLUSH BOLT FOR WOOD DOOR APPLICATION	1:1 5/8
ANSI:	UNIT:	VERSION:
---	inches (mm)	ver. 1.0 rev. 01/12
		BY:
		bteves/jsa