

# CAL-ROYAL

P R O D U C T S, I N C.

## T300 MAXIMUM SECURITY HEAVY-DUTY DEADBOLTS ANSI A156.5 GRADE 2

Available With Interchangeable Core

A Heavy Duty commercial quality deadbolt that provides a positive deterrent to forced entry. The cylinder recesses into the door to resist blows attempting to move the lock.

### CONSTRUCTION FEATURES



LISTED 3 HOURS,  
UL10C, UBC 7-2-1997  
(Optional)

Latch and strike screws are 8-32 x 1"  
combination wood/machine for applications  
on wood, metal or fiberglass doors and frames

wood frame reinforcer  
with 3" (76mm) screws

Dust box

Ergonomic thumb turn

Steel mounting  
Plate

Hardened  
steel tail piece

2 1/2" dia all metal one piece  
heavy duty tapered cylinder  
guard and metal insert

Pick resistant  
solid brass 6pin  
tumbler plug "C"

Brass Keys

One-piece steel housing  
for extra strength

Sturdy, all steel  
latch case and  
mechanism

1/4" (6mm)  
through bolts  
for high security

1" (25mm) throw  
high-strength steel  
alloy deadbolt with  
anti-saw pin



SINGLE CYLINDER T360 SERIES



DOUBLE CYLINDER T362 SERIES

### STANDARD ADJUSTABLE 2 3/4", 2 3/8" DEADLATCH SPECIFICATIONS

<b>Material</b>	:Wrought brass or stainless steel.
<b>Door Ranges</b>	:Adjustable 1 3/8" to 1 3/4" thickness.
<b>Backset</b>	:Adjustable 2 3/8" or 2 3/4". Optional UL listed. Prefix "UL" before part# for UL listed latch.
<b>Face Plate</b>	:Standard 2 1/4" x 1" packed with 1/8" plastic filler for 1 1/8" width.
<b>Bore Diameter</b>	:1" for latch, 2 1/8" for lock Housing.
<b>Keyway</b>	:6 pin high security "C" keyway. :Additional keyways: SCHLAGE C-K, SARGENT LA, RUSSWIN D1, FALCON/WEISER E, KWIKSET, CORBIN 60, ARROW, YALE 8, YALE GA.
<b>Finishes</b>	:US26D, US10B, US3, US26, US4 Other finishes available upon request, subject to lead time and quantity.
<b>Strike</b>	:1 1/8" x 2 3/4" square corner. Extra security 1" throw bolt with 1/4" free spinning anti-cut through pin. 3" screws with wood frame reinforcer greatly strengthens door frames.

Interchangeable core:  
Interchangeable core locks will accept compatible 6  
or 7 pin cores with BEST, FALCON and ARROW. Add  
"IC" before part number.

# CAL-ROYAL

P R O D U C T S, I N C.

6605 FLOTILLA ST., COMMERCE, CA 90040 U.S.A.

TEL: (323) 888-6601 FAX: (323) 888-6699

Website: cal-royal.com • Email: sales@cal-royal.com