

# INSTRUCTIONS FOR CAL-ROYAL OUTSIDE PULL TRIM FOR 77EO/7700V SERIES RIM AND VERTICAL ROD DEVICE



	77NL	77DTP	77EOP
<p>Cup washer &amp; screw</p> <p>Vertical Chassis Centerline</p>	<p>Cylinder Nut</p> <p>Cylinder Back Plate</p> <p>Rim Cylinder</p> <p>Cylinder screw</p> <p>Outside by pull &amp; Key. Key retracts latchbolt. Night Latch Pull Trim with cylinder</p>	<p>Outside by Pull only. Pull when dogged.</p>	<p>Outside by Cover Plate only.</p>
	<p><b>03 function Night Latch</b></p>	<p><b>02 function Pull</b></p>	<p><b>10 function Cover Plate</b></p>
	<p>Attach collar, back plate and rim cylinder to the trim plate with the (2) cylinder screws. Attach to door thru-bolting the (2) screws to the chassis &amp; (2) cup washer &amp; screws at the bottom to the door. Covers 161 cut out.</p>	<p>Attach trim to door thru-bolting the (2) screws to the chassis, &amp; (2) cup washers and screws at the bottom to the door. Covers 161 cut out.</p>	<p>Attach plate to door thru-bolting the (2) screws to the chassis. Covers 161 cut out.</p>