

# SC400 Series

## ELECTRIFIED MORTISE LOCKS

Available with or without deadbolt

### FEATURES:

- UL & CUL Listings; ANSI BHMA A156.25 Certified
- Continuous duty solenoids for cooler operation during "continuously on" applications
- Allows for an AC or DC power source through an appropriate power supply. No polarity.
- Low current draw
- Numerous switch options
- 3 year "No Hassle" warranty

### OPTIONS:

- Voltage requirement -12V AC / DC or 24V AC / DC
- Amperage - 600mA ±10% @ 12V or 300mA ±10% @ 24V
- Solenoid coil resistance - 12V = 20 Ω ±5% or 24V = 80 Ω ±5%
- Power consumption - 7.2 watts ±10%
- Function – available Fail Safe, "Electrically Locked" (EL) or Fail Secure, "Electrically Unlocked" (EU)

### RETROFITS SCHLAGE L9000

( direct chassis replacement )

### HOW TO ORDER ELECTRIFIED SC400 SERIES

- Use **SC Models** if ordered as an **ELECTRIFIED LOCK CASE ONLY**.
  - Use **ESC Models** if ordered as a complete lock with **ADD-ON** list price. Must Specify: SC Series item # and Electrification Option ( refer to table below ) separately.
- For Example: SC8080SS US26D with ESC400 ( EL 12V ) option,  
**Order: SC8080SS US26D and ESC400 as two line items.**

- **RX** – Request to Exit Switch (Monitors the inside handle)
- **LBM** – Latch Bolt Monitoring Switch (Monitors the position of latch bolt)
- **DPS** – Door Position Switch  
(\*Sold Separately. Not installed on the lock.)

**REFER TO PRICELIST  
FOR STOCK FINISHES AND FUNCTIONS**

ELECTRIFICATION OPTIONS ( WITHOUT DEADBOLT )							ELECTRIFIED LOCK CASE ONLY
MODEL #	EL	EU	12	24	RX	LBM	MODEL #
ESC400	✓		✓				SC400
ESC400-RX	✓		✓		✓		SC400-RX
ESC400-LBM	✓		✓			✓	SC400-LBM
ESC400-RXLBM	✓		✓		✓	✓	SC400-RXLBM
ESC404	✓			✓			SC404
ESC404-RX	✓			✓	✓		SC404-RX
ESC404-LBM	✓			✓		✓	SC404-LBM
ESC404-RXLBM	✓			✓	✓	✓	SC404-RXLBM
ESC408		✓	✓				SC408
ESC408-RX		✓	✓		✓		SC408-RX
ESC408-LBM		✓	✓			✓	SC408-LBM
ESC408-RXLBM		✓	✓		✓	✓	SC408-RXLBM
ESC412		✓		✓			SC412
ESC412-RX		✓		✓	✓		SC412-RX
ESC412-LBM		✓		✓		✓	SC412-LBM
ESC412-RXLBM		✓		✓	✓	✓	SC412-RXLBM

ELECTRIFICATION OPTIONS ( WITH DEADBOLT )							ELECTRIFIED LOCK CASE ONLY
MODEL #	EL	EU	12	24	RX	LBM	MODEL #
ESC416	✓		✓				SC416
ESC416-RX	✓		✓		✓		SC416-RX
ESC416-LBM	✓		✓			✓	SC416-LBM
ESC416-RXLBM	✓		✓		✓	✓	SC416-RXLBM
ESC420	✓			✓			SC420
ESC420-RX	✓			✓	✓		SC420-RX
ESC420-LBM	✓			✓		✓	SC420-LBM
ESC420-RXLBM	✓			✓	✓	✓	SC420-RXLBM
ESC424		✓	✓				SC424
ESC424-RX		✓	✓		✓		SC424-RX
ESC424-LBM		✓	✓			✓	SC424-LBM
ESC424-RXLBM		✓	✓		✓	✓	SC424-RXLBM
ESC428		✓		✓			SC428
ESC428-RX		✓		✓	✓		SC428-RX
ESC428-LBM		✓		✓		✓	SC428-LBM
ESC428-RXLBM		✓		✓	✓	✓	SC428-RXLBM

► Electrified Mortise Lock Case can be purchased separately. Refer to table above for options

# SC400 Series

## ELECTRIFIED MORTISE LOCKS

Available with or without deadbolt

### FEATURES:

- UL & CUL Listings; ANSI BHMA A156.25 Certified
- Continuous duty solenoids for cooler operation during "continuously on" applications
- Power Source: DC
- Low current draw
- Numerous switch options
- 1 year "No Hassle" warranty
- Voltage requirement - dual voltage 12-24V DC
- Amperage - 300mA @ 12V
- Solenoid coil resistance - 12V = 41 Ω
- Power consumption - approx. 7.2 watts = 24V  
approx. 3.6 watts = 12V
- Function – available Fail Safe, "Electrically Locked" (EL) or Fail Secure, "Electrically Unlocked" (EU)

### OPTIONS:


- **RX** – Request to Exit Switch (Monitors the inside handle)
- **LBM** – Latch Bolt Monitoring Switch (Monitors the position of latch bolt)
- **DPS** – Door Position Switch  
(\*Sold Separately. Not installed on the lock.)



**RETROFITS SCHLAGE L9000**  
( direct chassis replacement )

## NEW ALL-IN-ONE FEATURE

( Universal Dual Voltage 12 to 24 VDC,  
Field Convertible EL to EU & Vice Versa )



Complete Electrified  
Mortise Lock with SS Trim



Complete Electrified  
Mortise Lock with SE Trim

**REFER TO PRICELIST  
FOR STOCK FINISHES AND FUNCTIONS**

### ELECTRIFIED MORTISE LOCK WITH SS TRIM

#### ELECTRIFICATION OPTIONS ( WITHOUT DEADBOLT )

MODEL #	EL / EU	12-24V	RX	LBM
SC450-SS	✓	✓		
SC460-RX-SS	✓	✓	✓	
SC470-LBM-SS	✓	✓		✓
SC480-RXLBM-SS	✓	✓	✓	✓

#### ELECTRIFICATION OPTIONS ( WITH DEADBOLT )

MODEL #	EL / EU	12-24V	RX	LBM
SC455-SS	✓	✓		
SC465-RX-SS	✓	✓	✓	
SC475-LBM-SS	✓	✓		✓
SC485-RXLBM-SS	✓	✓	✓	✓

### ELECTRIFIED MORTISE LOCK WITH SE TRIM

#### ELECTRIFICATION OPTIONS ( WITHOUT DEADBOLT )

MODEL #	EL / EU	12-24V	RX	LBM
SC450-SE	✓	✓		
SC460-RX-SE	✓	✓	✓	
SC470-LBM-SE	✓	✓		✓
SC480-RXLBM-SE	✓	✓	✓	✓

#### ELECTRIFICATION OPTIONS ( WITH DEADBOLT )

MODEL #	EL / EU	12-24V	RX	LBM
SC455-SE	✓	✓		
SC465-RX-SE	✓	✓	✓	
SC475-LBM-SE	✓	✓		✓
SC485-RXLBM-SE	✓	✓	✓	✓