

22-3PT (Non-Fire Rated) & F22-3PT (Fire Rated)

Surface Vertical Rod, **Three-Point Latching** Exit Device,
ANSI A156.3 Grade 1, 3-Hour Rated, UL-Listed; Options: Alarm



ILLUSTRATION	ITEM #	DESCRIPTION	FINISHES
	NON-FIRE EXIT HARDWARE		
	22-3PT-3684	Surface Vertical Rod, 3-Point Type 36" x 84" *SH	ALUM, DURO
	22-3PT-4896	Surface Vertical Rod, 3-Point Type 48" x 96" *SH	
	FIRE EXIT HARDWARE RATED 3 HOURS (Includes thru-bolts)		
	F22-3PT-3684	Surface Vertical Rod, 3-Point Type 36" x 84" *SH	ALUM, DURO
	F22-3PT-4896	Surface Vertical Rod, 3-Point Type 48" x 96" *SH	
*SH Specify Left Hand Reverse (LHR) or Right Hand Reverse (RHR) for convenience.			

❖ ❖ ❖ **MUST ORDER TRIM SEPARATELY** ❖ ❖ ❖

PACKAGING INCLUDES

- (9pcs) Thru-Bolts for Fire-Rated Devices only.
- Strike Filler and Lock Front Filler included
- 4 pcs per master carton

NON-STOCK FINISHES

- Availability subject to minimum quantity and lead time. Consult factory.

ALARM AVAILABLE

- Alarm available. Prefix NALRM before PART#.

✦ **STANDARD DISCOUNT ONLY ON TRIMS AND ACCESSORIES** ✦

ITEM #	DESCRIPTION	FINISHES	UNIT
36ALARM22 ● IC36ALARM22 ● ICSC36ALARM22	Alarm kit for 36" Exit Devices	ALUM, DURO	Each
48ALARM22 ● IC48ALARM22 ● ICSC48ALARM22	Alarm kit for 48" Exit Devices		
NVALARM36 ● ICNVALARM36 ● ICSCNVALARM36	Alarm kit with micro switch for 36" Exit Devices		
NVALARM48 ● ICNVALARM48 ● ICSCNVALARM48	Alarm kit with micro switch for 48" Exit Devices		
620	Top Strike	---	
221	Handicap Bottom Strike		
233	Alternate Flush Mounting Bottom Strike		
N251	Overlapping strike		
406-3	Panic Surface Three-Point Type Shim Kit, 1/8" (Thick)		
412-3	Fire Rated Surface Three-Point Type Shim Kit, 1/8" (Thick)	ALUM, DURO	
EXTROD66-12	12" Extension Rod		
EXTROD66-24	24" Extension Rod	---	
LFF	Lock front filler (Zinc plated)		
SF	Strike filler (Zinc plated)		

● (IC) Indicates function available with **Best, Falcon & Arrow Interchangeable Core.**
● (ICSC) Indicates function available with **Schlage Full Size Format Interchangeable Core.**