

# Trim Selection

## ESCUTCHEON LEVER DESIGN

### CONSTRUCTION

- Rigid, non clutch mechanism.
- Thrubolted design.
- Non-handed design. Easily field reversible.
- Hardened steel heavy duty tailpiece.
- Standard 6-Pin Schlage "C" keyway rim cylinder included.

### ESCUTCHEON DIMENSIONS

2 3/4" width x 8 1/2" length. Lever length: 4 3/4".  
Fits and covers 2 1/8" 161 cutout

- ESC44-00 or
- ICESC4400 or
- ICSCESC4400

### ENTRANCE

Rigid Entrance, key locks or unlocks escutcheon trim  
ANSI Function (08)  
Operates as classroom function

### ESC44-30

### PASSAGE

Trim always operable and free  
ANSI Function (14)

### ESC44-40

### DUMMY

Dummy Escutcheon trim  
ANSI Function (02)

## THUMBPIECE TRIM

- THP4400 or
- ICTHP4400
- ICSTHP4400

### ENTRANCE

Key locks or unlocks thumbpiece.  
(Operates as classroom function)  
ANSI Function (05)

### THP4430

### PASSAGE

Trim always operable and free  
ANSI Function (15)

### ❖ ESCUTCHEON AND THUMBPIECE ❖

**DOOR THICKNESS:** Standard 1 3/4"

**FINISHES:** US26D Satin Chrome, DURO

**KEYWAY:** 6-Pin solid brass "C" keyway Rim Cylinder standard.  
Optional: Sargent LA-LB-LC and Kwikset.

- (IC) **INTERCHANGEABLE CORE:** Interchangeable Core locks will accept compatible 6 or 7-Pin cores with BEST, FALCON and ARROW.

- (ICSC) **INTERCHANGEABLE CORE:** Indicates function available with Schlage Full Size Format Interchangeable Core.



Anti-Microbial Coating available in US26D Only.  
Use part # "ANTB-TRIM" when ordering.

