




8600 Series

Automatic "LOW ENERGY" Swing Door Operator
ANSI A156.19 Low Energy Standard, UL325 Listed & UL991







HOW TO ORDER:

Must specify ITEM # + LENGTH + FINISH when ordering.

≽ eg. 8601-39 ALUM for 8601 with 39" length in Alum finish

STOCK ITEM PRICES IN BOLD NON-STOCK ITEMS AVAILABLE WITH FACTORY LEAD TIME AND SUBJECT TO MINIMUM ORDER

| TYPE | ITEM# | MOUNT | HANDING | TYPE OF ARM | | DESCRIPTION | LIMIT |
|---|-------|--|------------------------|------------------------|--------------------------|---|-------|
| | | | | ITEM# | Reveal | DESCRIPTION | UNIT |
| Single Operator | 8601 | Push | LHR | 8622-ARM | 0 - 14" | 1 unit, 1 controller, 1 cover, HANDED Standard size: 39" Optional size: 45" or 51" Add \$273.00 to List Price | |
| | 8602 | | RHR | | | | |
| | 8603 | Pull | LH | 8625-LH | 0 - 4" | | |
| | 8604 | | RH | 8624-RH | | | |
| | 8605 | | LH | 8626-ARM | 0 - 6" | | |
| | 8606 | | RH | | | | |
| Independent or Simultaneous Pair | 8607 | Push | LHR / RHR | 8622-ARM | 0 - 14" | 2 units, 2 controllers, 1 cover, | |
| | 8608 | Pull | LH / RH | 8625-LH & 8624-RH | 0 - 4" | NON-HANDED Standard size: 75" Optional size: 87" or 99" Add \$273.00 to List Price | Each |
| | 8609 | Pull | | 8626-ARM | 0 - 6" | | |
| Double Egress Independent or Simultaneous Pair | 8610 | Push / Pull LH / RHR LHR / RH LHR / RH LHR / RH | LH / RHR | 8625-LH & 8622-ARM | 0 - 4" & 0 - 14" | 2 units, 2 controllers, 1 cover, HANDED Standard size: 75" Optional size: 87" or 99" Add \$273.00 to List Price | |
| | 8611 | | LHR / RH | 8622-ARM & 8624-RH | 0 - 14" & 0 - 4" | | |
| | 8612 | | LH / RHR | 8626-ARM & 8622-ARM | 0 - 6" & 0 - 14" | | |
| | 8613 | | 8622-ARM & 8626-ARM | 0 - 14" & 0 - 6" | 7.00 (21000 to 2001 1100 | | |

for Optional Interior Operator, prefix "INT" before item #. (eg. 8601-39 ALUM with INT option will be "INT8601-39 ALUM)

NOTE: INTERIOR OPERATOR OPTION IS SUBJECT TO AVAILABILITY AND FACTORY LEAD TIME

► PACKAGING INCLUDES

- ➤ Low Energy Unit
- ➤ Safety Signage & Guideline Sticker
- > One Arm (either Push / Pull, specify Left / Right)

▶STOCK FINISHES

- ➤ Aluminum (ALUM)
- ➤ Dark Bronze (DB)
- > Consult factory for other finishes and sizes of the unit.
- > Price does not include Switches or Actuator.







▶ PARTS & ACCESSORIES FOR 8600 SERIES

| ILLUSTRATION | ITEM # | DESCRIPTION | UNIT |
|--------------|----------|--|-------|
| | 8622-ARM | Standard Push Arm, Non-Handed, for 0" to 14" reveal | |
| | 8623-EXT | Optional Push Arm Extension, center arm only. Non-Handed, for 14" to 20" reveal | |
| | 8624-RH | Angle Pull Arm, Right Handed, 0" to 4" reveal | Each |
| | 8625-LH | Angle Pull Arm, Left Handed, 0" to 4" reveal | |
| 60 | 8626-ARM | Optional Straight Pull Arm, Non-Handed, for 0" to 6" reveals | |
| | 8636-SW | 4.5" Square Stainless Steel Push Plate with blue handicap logo Includes surface mounting box (hard wired connection) | 1 set |
| | 8650-KIT | Basic 4.5" Square Push Plate package, Includes (2) 8636-SW (hard wired connection) | 1 set |
| | 8651-KIT | Basic 4.5" Square Push Plate package, Includes (2) 8636-SW, with 1 set of MTR-01 (wireless connection) | 1 set |





▶PARTS & ACCESSORIES FOR 8600 SERIES

| ILLUSTRATION | ITEM# | DESCRIPTION | UNIT |
|--------------|-----------|---|-------|
| | 8637-SW | 6" Round Stainless Steel Push Plate with blue handicap logo • Includes surface mounting box • (hard wired connection) | Each |
| | 8652-KIT | Basic 6" Round Push Plate package, Includes (2) 8637-SW (hard wired connection) | 1 set |
| | 8653-KIT | Basic 6" Round Push Plate package, Includes (2) 8637-SW, with 1 set of MTR-01 (wireless connection) | 1 set |
| | MTR-01 | Basic Radio Kit includes, 2 transmitters @ 433 MHz 1 receiver @ 433 MHz | 1 set |
| | SCAN-8660 | Infrared Safety Sensor door mounted length: 34.5" | Each |
| Push To | ACT-36 | 36" Vertical Actuator Bar with logo & text • (hard wired connection) | Each |
| OPEN C | ACT-900 | 36" Vertical Actuator Bar with logo & text • (900 MHz wireless connection) | EdUII |





▶ PARTS & ACCESSORIES FOR 8600 SERIES

| | · | | | |
|--|------------|--|-------|--|
| ILLUSTRATION | ITEM# | DESCRIPTION | UNIT | |
| Wave To Open | CTB-01 | Touchless Wave to Open Switch with Text, Logo & Hand | | |
| Wave To Open Mg | CTB-02 | Touchless Wave to Open Switch with Text, Logo & Hand | | |
| (((^{(†}))) | CTB-03 | Touchless Wave to Open Switch with Text & Hand active infrared sensing technology, 1"- 6" range includes surface mount plastic box 4.5" x 4.5" Stainless Steel & Glass plate Power: 12V - 24V DC (hard wired connection) | Each | |
| © Wave To Open Φ | CTB-05 | Touchless Wave to Open Switch with Text & Hand • infrared photoelectric reflective sensor, 2"- 8" range • fits in a standard jamb size electrical box • 1.5" x 4.5" Stainless Steel plate • Power: 12V - 24V DC • weather resistant & adustable timer delay, • red / green LED indicator • (hard wired connection) | | |
| Wave To Open W | CTB-07 | Touchless Wave to Open Switch with Text, Logo & Hand infrared photoelectric reflective sensor, 2"- 8" range includes surface mount plastic box 4.5" x 4.5" Stainless Steel plate Power: 12V - 24V DC weather resistant & adustable timer delay red / green LED indicator (hard wired connection) | | |
| THE STATE OF THE S | CTW-02 KIT | Touchless Wave to Open Switch Kit includes: (2) Touchless Wireless Switch with transmitter & (1) Receiver 900 MHz. active infrared sensing technology 1"- 3" range 4.5" x 4.5" Composite surface includes surface mount plastic box Power: 12V - 24V DC (wireless connection) | 1 set | |





▶ PARTS & ACCESSORIES FOR 8600 SERIES

| ILLUSTRATION | ITEM# | DESCRIPTION | UNIT | |
|--|---------|---|-------|--|
| ₩AVE TO WAVE TO OPEN ⊕ | 8630-SW | Touchless Switch (text & hand) • with microwave motion technology • 4.5" x 4.5", double gang • 2" - 24" detection range • (hard wired connection) | | |
| | 8640-SM | Surface Mount Box, double gang • can be used with 8630-SW & 8633-SW • 4.5" x 4.5", square | | |
| WAVE TO OPEN ⊕ | 8631-SW | Touchless Switch (text & hand) • with microwave motion technology • 4.5" x 2.75", single gang • 2" - 24" detection range • (hard wired connection) | Each | |
| | 8641-SM | Surface Mount Box, single gang can be used with 8631-SW & 8633-SW 4.5" x 2.75" | | |
| WAVE TO OPEN | 8632-SW | Touchless Switch (text & hand) with microwave motion technology 4.5" x 1.68", jamb mount 2" - 24" detection range (hard wired connection) | | |
| | 8642-SM | Jamb Surface Mount Box • can be used with 8632-SW • 1.5" x 4.75" | | |
| MANY TO OPEN WHATE T | 8633-SW | Touchless Switch (text & hand) • with microwave motion technology • comes with both single and double gang face plates • 4" - 24" detection range • can be used with 8640-SM & 8641-SM • (hard wired connection) | 1 set | |
| WAVE TO OPEN | 8634-SW | 6" Round Touchless Switch (text, logo & hand) with microwave motion technology short range detection (hard wired connection) | | |
| WAVE TO OPEN | 8635-SW | 4.75" Square Touchless Switch (text, logo & hand) with microwave motion technology short range detection (hard wired connection) | Each | |