


## 98-3PT (Non-Fire Rated) & F98-3PT (Fire Rated)

Surface Vertical Rod, **Three-Point Latching** Exit Device,  
ANSI A156.3 Grade 1, 3-Hour Rated, UL-Listed; Options: Alarm



| ILLUSTRATION   | ITEM #  | DESCRIPTION   | FINISHES                 |
|--|---|---|--------------------------|
|  | <b>NON-FIRE EXIT HARDWARE</b>                                 |   |                          |
|  | 98-3PT-3684   | Surface Vertical Rod, 3-Point Type<br>36" x 84" *SH | US32D, US10B, L1 (BLACK) |
|  | 98-3PT-4896   | Surface Vertical Rod, 3-Point Type<br>48" x 96" *SH |                          |
|  | <b>FIRE EXIT HARDWARE RATED 3 HOURS (Includes thru-bolts)</b> |   |                          |
|  | F98-3PT-3684  | Surface Vertical Rod, 3-Point Type<br>36" x 84" *SH | US32D, US10B, L1 (BLACK) |
|  | F98-3PT-4896  | Surface Vertical Rod, 3-Point Type<br>48" x 96" *SH |                          |
| *SH Specify Left Hand Reverse (LHR) or Right Hand Reverse (RHR) for convenience. |   |   |                          |

❖ ❖ ❖ **MUST ORDER TRIM SEPARATELY** ❖ ❖ ❖

#### PACKAGING INCLUDES

- (9pcs) Thru-Bolts for Fire-Rated Devices only.
- Strike Filler and Lock Front Filler included
- 4 pcs per master carton

#### ALARM AVAILABLE

- Alarm available. Prefix NALRM before PART#.

#### NON-STOCK FINISHES

- Availability subject to minimum quantity and lead time. Consult factory.

#### ANTI-MICROBIAL

- Available on US32D finish Only.
- Use part # ANTB-EXIT.

★ **STANDARD DISCOUNT ONLY ON TRIMS AND ACCESSORIES** ★

| ITEM #  | DESCRIPTION  | FINISHES     | UNIT |
|---|--|--------------|------|
| 36ALARM98<br>● IC36ALARM98<br>● ICSC36ALARM98 | Alarm kit for 36" Exit Devices                             | US10B, US32D | Each |
| 48ALARM98<br>● IC48ALARM98<br>● ICSC48ALARM98 | Alarm kit for 48" Exit Devices                             |              |      |
| NVALARM36<br>● ICNVALARM36<br>● ICSCNVALARM36 | Alarm kit with micro switch for 36" Exit Devices           |              |      |
| NVALARM48<br>● ICNVALARM48<br>● ICSCNVALARM48 | Alarm kit with micro switch for 48" Exit Devices           |              |      |
| 620   | Top Strike   | ---          |      |
| 221   | Handicap Bottom Strike                                     |              |      |
| 233   | Alternate Flush Mounting Bottom Strike                     |              |      |
| N251  | Overlapping strike   |              |      |
| 806-3   | Panic Surface Three-Point Type Shim Kit, 1/8" (Thick)      |              |      |
| 812-3   | Fire Rated Surface Three-Point Type Shim Kit, 1/8" (Thick) | US32D        |      |
| EXTROD66-12                                   | 12" Extension Rod  |              |      |
| EXTROD66-24                                   | 24" Extension Rod  |              |      |
| LFF   | Lock front filler (Zinc plated)                            | ---          |      |
| SF  | Strike filler (Zinc plated)                                |              |      |

● (IC) Indicates function available with **Best, Falcon & Arrow Interchangeable Core**.  
● (ICSC) Indicates function available with **Schlage Full Size Format Interchangeable Core**.