

MISCELLANEOUS DOOR AND WINDOW HARDWARE

ILLUSTRATION	ITEM	SIZE	ITEM #	FINISH
	<p style="text-align: center;">Latch Guard Protector with Security Frame Pin</p> <ul style="list-style-type: none"> ▶ For out-opening doors ▶ For use with mortise or cylindrical locks ▶ Used with security frame pin to prevent separation of the door and frame ▶ Conforms with ANSI / BHMA A156.2 Series 4000 ▶ Similar to Glynn Johnson #LG1 	Dimensions: 3" x 11 1/2"	GJLPG2	US32D
	<p style="text-align: center;">Latch Guard Protector with Escutcheon Cut-Out</p> <ul style="list-style-type: none"> ▶ For out-opening doors ▶ For use with mortise, deadbolts, and cylindrical locksets with 2 3/4" backset ▶ Conforms with ANSI / BHMA A156.2 Series 4000 	Dimensions: 3 1/2" x 11 3/4"	LG28	Alum, Duro, Gold, US26D
	<p style="text-align: center;">Brass Dust Proof Strike</p> <ul style="list-style-type: none"> ▶ Spring tension calibrated for positive closing and eliminates binding ▶ Can be locked in up position ▶ Conforms to ANSI / BHMA A156.16 L14011 	Dimensions: Face Plate: 1 3/8" x 2 7/8" Barrel: 1" dia. Depth: 2 1/4"	DPSTRK1	US26D, 26, US3, 10B, US1
	<p style="text-align: center;">Stainless Steel Dust Proof Strike</p> <ul style="list-style-type: none"> ▶ For use with attaching bottom bolt of a flushbolt ▶ Spring-loaded plunger will return to the threshold level when flush bolt is retracted, preventing the build up of dust and debris from the floor ▶ Conforms to ANSI / BHMA A156.16 L14011 	Dimensions: Face Plate: 1" dia., 1/8" thick Body: 3/4" dia., 1 7/16" depth Strike Hole: 1/2" dia.	DPSTRK-39 NEW ITEM	US32D
	<p style="text-align: center;">Heavy Duty Roller Catch</p> <ul style="list-style-type: none"> ▶ Adjustable Nylon Roller with Square Heavy Duty Cast 2 1/4" Full-Lip Strike ▶ Conforms to ANSI / BHMA A156.16, E19091 	Dimensions: Face Plate: 1" x 3 3/8" Full Lip Strike: 1/8" x 1" x 3 3/8" Depth: 1 13/16"	ARL-1338	US3, 26, US19, 15, US5, 15A, US10B, 26D
	<p style="text-align: center;">Optional T-Strike for Heavy Duty Roller Catch ARL1338</p> <ul style="list-style-type: none"> ▶ Architectural finishes available ▶ Packed with screws 	Dimensions: 2 3/4" x 1 1/2" x 1 3/4"	ARLTSTRK62	US3, 26, US19, 15, US5, 15A, US10B, 26D