



PART#
CR336436

FINISH: MILL FINISH ALUMINUM

7/16" (11.1 mm)
CARPET/SPECIAL
PURPOSE THRESHOLD

7/16" H x 4" W x 36" L
11.1 mm x 101.6 mm x 914.4 mm

INSTALLATION INSTRUCTIONS

1. Measure width at the bottom of the frame and cut the threshold to exact full width of the opening.
2. If necessary trim and notch the threshold ends to accommodate the side jamb stops.
3. Mark and drill pilot holes through the pre-drilled holes in the threshold and fasten with screws provided.
4. Seal both ends and along the sides of the threshold.
5. Operate the door multiple times to ensure proper adjustment so as not to prevent the door from self-closing and latching.



Meets UL10B, UL10C and UBC 7-2 (1997) Category J



3 HR POSITIVE PRESSURE

MATERIAL FOR USE IN LISTED STEEL FRAMES AND CLASSIFIED HOLLOW METAL STEEL COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 3 HOURS, WOOD COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 1-1/2 HOURS, AND WOOD CORE FIRE DOORS ARE RATED 20 MINUTES WITHOUT HOSE STREAM.



PART#
CR336436

FINISH: DARK BRONZE ANODIZED ALUMINUM

7/16" (11.1 mm)
CARPET/SPECIAL
PURPOSE THRESHOLD

7/16" H x 4" W x 36" L
11.1 mm x 101.6 mm x 914.4 mm

INSTALLATION INSTRUCTIONS

1. Measure width at the bottom of the frame and cut the threshold to exact full width of the opening.
2. If necessary trim and notch the threshold ends to accommodate the side jamb stops.
3. Mark and drill pilot holes through the pre-drilled holes in the threshold and fasten with screws provided.
4. Seal both ends and along the sides of the threshold.
5. Operate the door multiple times to ensure proper adjustment so as not to prevent the door from self-closing and latching.



Meets UL10B, UL10C and UBC 7-2 (1997) Category J



3 HR POSITIVE PRESSURE

MATERIAL FOR USE IN LISTED STEEL FRAMES AND CLASSIFIED HOLLOW METAL STEEL COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 3 HOURS, WOOD COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 1-1/2 HOURS, AND WOOD CORE FIRE DOORS ARE RATED 20 MINUTES WITHOUT HOSE STREAM.



PART#
CR336448

FINISH: MILL FINISH ALUMINUM

7/16" (11.1 mm)
CARPET/SPECIAL
PURPOSE THRESHOLD

7/16" H x 4" W x 48" L
11.1 mm x 101.6 mm x 1219.2 mm

INSTALLATION INSTRUCTIONS

1. Measure width at the bottom of the frame and cut the threshold to exact full width of the opening.
2. If necessary trim and notch the threshold ends to accommodate the side jamb stops.
3. Mark and drill pilot holes through the pre-drilled holes in the threshold and fasten with screws provided.
4. Seal both ends and along the sides of the threshold.
5. Operate the door multiple times to ensure proper adjustment so as not to prevent the door from self-closing and latching.



Meets UL10B, UL10C and
UBC 7-2 (1997) Category J



**3 HR POSITIVE
PRESSURE**

MATERIAL FOR USE IN LISTED STEEL FRAMES AND CLASSIFIED HOLLOW METAL STEEL COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 3 HOURS, WOOD COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 1-1/2 HOURS, AND WOOD CORE FIRE DOORS ARE RATED 20 MINUTES WITHOUT HOSE STREAM.



PART#
CR336448

FINISH: DARK BRONZE ANODIZED ALUMINUM

7/16" (11.1 mm)
CARPET/SPECIAL
PURPOSE THRESHOLD

7/16" H x 4" W x 48" L
11.1 mm x 101.6 mm x 1219.2 mm

INSTALLATION INSTRUCTIONS

1. Measure width at the bottom of the frame and cut the threshold to exact full width of the opening.
2. If necessary trim and notch the threshold ends to accommodate the side jamb stops.
3. Mark and drill pilot holes through the pre-drilled holes in the threshold and fasten with screws provided.
4. Seal both ends and along the sides of the threshold.
5. Operate the door multiple times to ensure proper adjustment so as not to prevent the door from self-closing and latching.



Meets UL10B, UL10C and
UBC 7-2 (1997) Category J



**3HR POSITIVE
PRESSURE**

MATERIAL FOR USE IN LISTED STEEL FRAMES AND CLASSIFIED HOLLOW METAL STEEL COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 3 HOURS, WOOD COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 1-1/2 HOURS, AND WOOD CORE FIRE DOORS ARE RATED 20 MINUTES WITHOUT HOSE STREAM.



PART#
CR336472

FINISH: MILL FINISH ALUMINUM

7/16" (11.1 mm)
CARPET/SPECIAL
PURPOSE THRESHOLD

7/16" H x 4" W x 72" L
11.1 mm x 101.6 mm x 1828.8 mm

INSTALLATION INSTRUCTIONS

1. Measure width at the bottom of the frame and cut the threshold to exact full width of the opening.
2. If necessary trim and notch the threshold ends to accommodate the side jamb stops.
3. Mark and drill pilot holes through the pre-drilled holes in the threshold and fasten with screws provided.
4. Seal both ends and along the sides of the threshold.
5. Operate the door multiple times to ensure proper adjustment so as not to prevent the door from self-closing and latching.



Meets UL10B, UL10C and UBC 7-2 (1997) Category J



3 HR POSITIVE PRESSURE

MATERIAL FOR USE IN LISTED STEEL FRAMES AND CLASSIFIED HOLLOW METAL STEEL COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 3 HOURS, WOOD COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 1-1/2 HOURS, AND WOOD CORE FIRE DOORS ARE RATED 20 MINUTES WITHOUT HOSE STREAM.



PART#
CR336472

FINISH: DARK BRONZE ANODIZED ALUMINUM

7/16" (11.1 mm)
CARPET/SPECIAL
PURPOSE THRESHOLD

7/16" H x 4" W x 72" L
11.1 mm x 101.6 mm x 1828.8 mm

INSTALLATION INSTRUCTIONS

1. Measure width at the bottom of the frame and cut the threshold to exact full width of the opening.
2. If necessary trim and notch the threshold ends to accommodate the side jamb stops.
3. Mark and drill pilot holes through the pre-drilled holes in the threshold and fasten with screws provided.
4. Seal both ends and along the sides of the threshold.
5. Operate the door multiple times to ensure proper adjustment so as not to prevent the door from self-closing and latching.



Meets UL10B, UL10C and UBC 7-2 (1997) Category J



3 HR POSITIVE PRESSURE

MATERIAL FOR USE IN LISTED STEEL FRAMES AND CLASSIFIED HOLLOW METAL STEEL COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 3 HOURS, WOOD COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 1-1/2 HOURS, AND WOOD CORE FIRE DOORS ARE RATED 20 MINUTES WITHOUT HOSE STREAM.



PART#
CR336496

FINISH: MILL FINISH ALUMINUM

7/16" (11.1 mm)
CARPET/SPECIAL
PURPOSE THRESHOLD

7/16" H x 4" W x 96" L
11.1 mm x 101.6 mm x 2438.4 mm

INSTALLATION INSTRUCTIONS

1. Measure width at the bottom of the frame and cut the threshold to exact full width of the opening.
2. If necessary trim and notch the threshold ends to accommodate the side jamb stops.
3. Mark and drill pilot holes through the pre-drilled holes in the threshold and fasten with screws provided.
4. Seal both ends and along the sides of the threshold.
5. Operate the door multiple times to ensure proper adjustment so as not to prevent the door from self-closing and latching.



Meets UL10B, UL10C and UBC 7-2 (1997) Category J



3 HR POSITIVE PRESSURE

MATERIAL FOR USE IN LISTED STEEL FRAMES AND CLASSIFIED HOLLOW METAL STEEL COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 3 HOURS, WOOD COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 1-1/2 HOURS, AND WOOD CORE FIRE DOORS ARE RATED 20 MINUTES WITHOUT HOSE STREAM.



PART#
CR336496

FINISH: DARK BRONZE ANODIZED ALUMINUM

7/16" (11.1 mm)
CARPET/SPECIAL
PURPOSE THRESHOLD

7/16" H x 4" W x 96" L
11.1 mm x 101.6 mm x 2438.4 mm

INSTALLATION INSTRUCTIONS

1. Measure width at the bottom of the frame and cut the threshold to exact full width of the opening.
2. If necessary trim and notch the threshold ends to accommodate the side jamb stops.
3. Mark and drill pilot holes through the pre-drilled holes in the threshold and fasten with screws provided.
4. Seal both ends and along the sides of the threshold.
5. Operate the door multiple times to ensure proper adjustment so as not to prevent the door from self-closing and latching.



Meets UL10B, UL10C and UBC 7-2 (1997) Category J



3 HR POSITIVE PRESSURE

MATERIAL FOR USE IN LISTED STEEL FRAMES AND CLASSIFIED HOLLOW METAL STEEL COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 3 HOURS, WOOD COMPOSITE TYPE FIRE DOORS ARE RATED UP TO AND INCLUDING 1-1/2 HOURS, AND WOOD CORE FIRE DOORS ARE RATED 20 MINUTES WITHOUT HOSE STREAM.