

GENESYS SERIES

Electrified Cylindrical Lock

► **Electrified Part #ELEC**
(Specify Options)

FEATURES:

- UL Listed
- Continuous duty solenoids for cooler operation during “*continuously ON*” applications
- Standard plug-in rectifier allows for an AC/DC power source
- Low current draw
- 3 year “No Hassle” warranty

OPTIONS:

- Voltage requirement - 12V (AC/DC) or 24V (AC/DC)
- Amperage – 250mA @ 12V or 150mA @ 24V
- Solenoid coil resistance - 12V = 49 Ω or 24V = 159 Ω
- Power consumption - 3 watts
- Function – available “Fail Safe” (FS) or “Fail Secure” (FSE)



GENESYS ELECTRIFIED
CYLINDRICAL LOCK

ELECTRIFIED	
ITEM #	DESCRIPTION
ECGN0512SAF	FAIL SAFE OPTION 12V AC / DC
⚡ EICGN0512SAF	
⚡ EICGYS0512SAF	
ECGN0512SEC	FAIL SECURE OPTION 12V AC / DC
⚡ EICGN0512SEC	
⚡ EICGYS0512SEC	
ECGN0524SAF	FAIL SAFE OPTION 24V AC / DC
⚡ EICGN0524SAF	
⚡ EICGYS0524SAF	
ECGN0524SEC	FAIL SECURE OPTION 24V AC / DC
⚡ EICGN0524SEC	
⚡ EICGYS0524SEC	