

GVEV.R13329 - Swinging Fire Door Closers

Swinging Fire Door Closers

See General Information for Swinging Fire Door Closers

CAL-ROYAL PRODUCTS INC

R13329

6605 FLOTILLA ST

COMMERCE, CA 90040-1815 USA

For self closing door closers, without hold-open feature, floor mounted type, size 2-4 Model(s) CR075

For self closing door closers, without hold-open feature, floor mounted type, size 3 Model(s) CR084, CR128, CR130, CR220, CR6601

For self closing door closers, without hold-open feature, surface mounted type, size 3, Model(s) EU430CE

For self-closing doors, concealed mounted type, size 2 Model(s) CR271PC pocket closer

For self-closing doors, fixed size 3, without hold-open feature, overhead concealed type Model(s) 8860

For self-closing doors, surface mounted type, size 2 Model(s) 710 Series

For self-closing doors, surface mounted type, size 4 Model(s) 700 Series

For self-closing doors, surface mounted type, without hold-open feature, size 1-6 Model(s) 800 Series+, 900 Series+, CR441+

For self-closing doors, surface mounted type, without hold-open feature, size 2-5 Model(s) 300 Series, 500 Series+

For self-closing doors, surface-mounted type Model(s) 420-P, 430-P, 440-P, 450-P, 500PBF, 720, 730, 730BC, 740, 740BC, 750, 750BC, CR441, CR441DA, CR801, CR801DA, CR801S, CR801SDA, N900PBF, N900PBFDA

For self-closing doors, surfaced-mounted type Model(s) 300-P(3-6)BC+COV, 300-PBF(1-4)BC+COV, 430-PBC, 440-PBC, 440F-PBC

For self-closing doors, without hold-open feature, concealed mounted type, size 2-3 Model(s) CR096

For self-closing doors, without hold-open feature, spring hinge type Model(s) NBENSH4458R, NEWSCSH35, NEWSH140, NEWSH3558R, NEWSH35R, NEWSH4458R, NEWSH44R, NEWSH454

For self-closing doors, without hold-open feature, spring hinge type, 4-1/2 in. or 114 MM size Model(s) Grade 1



For self-closing doors, without hold-open feature, surface mounted type Model(s) 300 Series, 420-P Series, 430-P Series, 440-P Series, 450-P Series, 700 Series, 700BC Series, CR4041 Series

Investigated to Standard UL 10C.

For self-closing doors, adjustable sizes 1 to 4, without hold-open feature, Overhead Concealed type Model(s) 8800, 8810, 8820, 8830, 8840, 8850

For self-closing doors, surface-mounted type Model(s) 300P COV, 300PBF COV, 440F-P, 450-PBC

Note - Above devices have been evaluated in accordance with Standard UL 10C designed to be used with swinging type fire doors rated up to and including 3 hours.

Trademark and/or Tradename:  , 

Last Updated on 2020-09-04

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

