

GXSR.R14281 - Flush and Surface Bolts, Manual Type

Flush and Surface Bolts, Manual Type

See General Information for Flush and Surface Bolts, Manual Type

CAL-ROYAL PRODUCTS INC

R14281

6605 FLOTILLA ST

COMMERCE, CA 90040-1815 USA

Manual flush bolts, Model MF6341 with 7/8 in. throw, for hollow-metal steel stiffened and steel covered composite doors rated up to and including 1-1/2 hr.

Model WF6341 with 7/8 in. throw, for fire rated wood composite, and wood core doors rated up to and including 1-1/2 hr.

Model FBS-100 with min. 3/4 inch throw for use on swinging doors measuring up to 4 ft. wide and 8 ft. high rated up to and including 3 hrs.

Manual surface bolts, Model UL453.

Model UL831 with 1 in. latch throw.

Last Updated on 2018-11-13

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"