

INSTRUCTIONS FOR CAL-ROYAL OUTSIDE PULL TRIM FOR 99EO/99V SERIES RIM AND VERTICAL ROD DEVICE



	99NL	99DTP	99EOP
<p>Cup washer & screw</p> <p>Vertical Chassis Centerline</p>	<p>Cylinder Nut</p> <p>Cylinder Back Plate</p> <p>Rim Cylinder</p> <p>Cylinder screw</p> <p>Outside by pull & Key. Key retracts latchbolt. Night Latch Pull Trim with cylinder</p>	<p>Outside by Pull only. Pull when dogged.</p>	<p>Outside by Cover Plate only.</p>
	<p>03 function Night Latch</p>	<p>02 function Pull</p>	<p>10 function Cover Plate</p>
	<p>Attach collar, back plate and rim cylinder to the trim plate with the (2) cylinder screws. Attach to door thru-bolting the (2) screws to the chassis & (2) cup washer & screws at the bottom to the door. Covers 161 cut out.</p>	<p>Attach trim to door thru-bolting the (2) screws to the chassis, & (2) cup washers and screws at the bottom to the door. Covers 161 cut out.</p>	<p>Attach plate to door thru-bolting the (2) screws to the chassis. Covers 161 cut out.</p>