

NOTE: ALL Fire Rated application are required to use the sex bolts.

LOCATE DRILL & TAP THESE
HOLE WHEN APPLYING
HARDWARE TO DOOR

41" From Finish Floor

INSIDE FACE
OF DOOR

VERTICAL REFERENCE LINE

#10-24 TAPPED HOLE (4 REQUIRED)

2-1/8 DIA. THRU DOOR
IF USED WITH CYLINDRICAL TRIM

Ø OF LATCH BOLT AND
HORIZONTAL REFERENCE LINE

#10-24 TAPPED HOLES

VERTICAL
REFERENCE LINE

Ø OF CHASSIS

SEE NOTE 3

DOOR EDGE


2-5/8"

8-1/2"

2-7/16"
2-11/16"
2-1/4"

1. TOLERANCE OF ALL DIMENSIONS $\pm 1/64"$.
2. WE RECOMMEND THAT ALL TAPPED HOLES BE DRILLED & TAPPED IN FIELD
3. IF LOCK STILE IS 4-1/2" WIDE OR WIDER DIM IS 2-3/4"
4. SURFACE OF DOOR WHERE EXIT DEVICE IS TO BE APPLIED MUST BE FLUSH.

The illustration and technical description in this cut sheet is current as of the date in version date on the right. Cal-Royal Product reserves the right to, and may, on occasions, make changes and/or improvements in designs and dimensions without prior notice.

	6605 Flotilla Street City of Commerce CA 90040 USA Tel.# (323) 888-6601 FAX # (323) 888-6699 WEB SITE: CAL-ROYAL.COM Email: sales@cal-royal.com	ITEM NO.	DESCRIPTION :	NOT TO SCALE	UNIT	Prepared By:	DATE	DWG. NO.
		AF9800	PANIC FIRE RATED RIM EXIT DEVICE		PRIMARY DIMENSION SHOWN IN INCHES	BBT / ADG / CVL	04/08/2028	EDT-4148A-04/25-1 of 1
					PAGE 1 OF 1			REV: Ver-01